

CARÁCTERÍSTICAS



MEDIDAS	12 - 17
SERIES	50 - 80
IND. VELOCIDAD	H - V



PASSENGER CAR TIRE

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERAL WITH(mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
12	145/70R12	69	T	150	509	6.5	325	300	E	E	1
13	155/65R13	73	T	157	532	7.5	365	300	-	-	-
	155/70R13	75	T	157	548	7.5	387	300	-	-	-
	155/80R13	79	T	157	578	7.5	437	300	-	-	-
	165/65R13	77	T	170	544	7.5	412	300	E	E	2
	165/70R13	79	H	-	562	7.5	437	300	E	C	1
	165/70R13	79	T	170	562	7.5	437	300	E	E	1
	165/80R13	83	T	165	594	7.5	487	300	-	-	-
	175/60R13	77	T	177	540	7.5	412	300	-	-	-
	175/65R13	80	T	177	558	7.5	450	300	-	-	-
	175/70R13	82	T	177	576	7.5	475	300	E	E	1
	175/75R13	84	T	177	594	7.5	500	300	E	E	1
	185/70R13	86	T	189	590	8	530	300	E	E	2
14	155/65R14	75	T	157	558	7.5	387	300	-	-	-
	155/70R14	77	T	157	574	6.8	412	300	-	-	-
	165/60R14	75	H	170	554	7.5	387	300	E	E	1
	165/65R14	79	H	-	570	7.5	437	300	E	C	1
	165/65R14	79	T	170	570	7.5	437	300	E	E	2
	165/70R14	81	T	170	588	7.5	462	300	-	-	-
	175/60R14	79	H	177	566	7.5	437	300	-	-	-
	175/65R14	82	H	177	584	8	475	300	E	C	2
	175/65R14 XL	86	T	-	584	-	-	-	E	C	1
	175/65R14	82	T	-	584	8	475	300	E	E	1
	175/70R14	84	T	177	602	8	560	340	E	E	1
	175/70R14 XL	88	T	177	602	8	560	340	E	C	1
	175/75R14	86	T	194	618	7.5	530	300	E	E	-
	185/55R14	80	H	189	560	6.8	450	300	-	-	-
	185/60R14	82	H	189	578	7.5	475	300	E	C	1
	185/65R14	86	H	-	596	8	530	300	E	C	2
	185/65R14	86	T	-	596	8	530	300	E	E	1
	185/70R14	88	H	-	616	8	560	300	E	E	2
	185/70R14	88	T	-	616	8	560	300	E	E	1
	195/60R14	86	H	-	590	8	590	300	E	C	2
	195/60R14	86	T	201	590	8	530	300	E	E	2
	195/65R14	89	H	201	610	8	580	300	E	C	2
	195/70R14	91	H	-	630	8	615	300	F	E	2
	195/70R14	91	T	201	630	8	615	300	E	E	2
	205/60R14	88	H	209	602	7.5	560	300	E	C	2
	205/70R14	95	H	209	644	8	690	300	E	E	2
	205/70R14 XL	98	H	-	644	-	-	-	E	E	2
	215/70R14	96	H	-	658	8	710	300	E	E	2
	215/70R14	96	T	221	658	8	710	300	E	E	2

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERAL WITH (mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
15	145/65R15	72	T	150	569	6.8	355	300	-	-	-
	165/60R15 XL	81	H	170	579	6.8	462	340	-	-	-
	165/65R15	81	T	170	595	6.8	462	300	-	-	-
	175/55R15	77	V	182	573	6.8	412	300	-	-	-
	175/60R15	81	H	177	591	6.8	462	300	-	-	-
	175/65R15	84	H	177	609	8	500	300	E	C	2
	185/55R15	82	H	-	585	8	475	300	E	C	2
	185/55R15	82	V	194	585	8	475	300	E	C	2
	185/60R15	84	H	-	-	-	-	-	E	C	2
	185/60R15 XL	88	H	189	603	8	560	340	E	E	2
	185/65R15	88	H	189	621	8	560	300	E	C	2
	185/65R15	88	T	-	621	8	560	300	E	E	2
	195/50R15	82	V	201	577	8	475	300	E	B	2
	195/55R15	85	H	-	595	8	515	300	E	C	2
	195/55R15	85	V	201	595	8	515	300	E	B	1
	195/60R15	88	H	201	615	8	560	300	E	C	2
	195/60R15	88	V	-	615	8	-	-	E	C	2
	195/65R15	91	H	-	635	8	615	300	E	C	2
	195/65R15	91	V	201	635	8	615	300	E	C	2
	205/60R15	91	V	209	627	8	615	300	E	C	2
	205/65R15	94	H	209	647	8.5	670	300	E	C	2
	205/65R15	94	V	-	647	8.5	670	300	E	C	2
	205/70R15	96	H	209	669	8	710	300	E	C	2
	205/70R15 XL	100	H	-	669	-	-	-	C	B	2
	205/70R15	96	T	209	669	8	710	300	E	E	1
	215/60R15	94	H	221	639	8	670	300	E	C	2
	215/65R15	96	H	221	661	8	710	300	E	C	2
	215/70R15	98	H	221	683	8	750	300	E	E	2
	225/60R15	96	V	228	651	8	710	300	E	C	2
16	175/50R16	77	V	182	582	6.8	412	300	-	-	-
	185/50R16	81	V	194	592	6.8	462	300	E	E	2
	185/55R16	83	V	194	610	6.8	487	300	E	-	-
	195/50R16	84	V	201	602	8	500	300	E	E	2
	195/55R16	87	V	201	620	8	545	300	E	C	2
	195/60R16	89	H	201	640	8	580	300	E	C	2
	205/55R16	91	H	-	632	8	615	300	E	C	2
	205/55R16	91	V	214	632	8	615	300	E	C	2
	205/60R16	92	H	-	652	8	630	300	E	C	2
	205/60R16	92	V	209	652	8	630	300	E	C	2
	205/65R16	95	H	209	672	8	690	300	E	C	2
	215/55R16	93	V	226	642	8	650	300	E	C	2
	215/60R16 XL	99	H	221	664	8	775	340	E	E	2
	215/60R16	95	V	-	664	-	-	-	E	C	2

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERAL WITH (mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
16	215/65R16	98	H	221	686	8	750	300	E	C	2
	225/55R16	95	V	233	654	8	690	300	E	C	2
	225//60R16	98	H	-	676	8	750	300	E	C	2
	225/60R16	98	V	228	676	8	750	300	E	C	2
	225/65R16	100	T	228	698	8	800	300	-	-	-
	235/60R16	100	H	240	688	8	800	300	E	C	2
	235/65R16	103	T	240	712	8	875	300	-	-	-
17	215/55R17 XL	98	H	-	668	-	-	-	C	B	2
	215/55R17	94	V	226	668	8	670	300	E	C	2
	215/60R17	96	T	221	690	7.7	710	300	-	-	-
	215/65R17	99	T	221	712	8	775	300	-	-	-
	225/55R17 XL	101	H	233	680	8	825	340	E	E	2
	225/60R17	99	H	228	702	8	775	300	E	C	2
	225/65R17	102	H	228	724	8	850	300	E	C	2
	235/65R17	104	H	240	738	8	900	300	-	-	-