

CARÁCTERÍSTICAS



EFICIENCIA



ADHERENCIA



SIMETRICA



TRACCIÓN



ON & OFF



DRENAJE

MEDIDAS	15 - 22
SERIES	50 - 75
IND. VELOCIDAD	L - T



PASSENGER CAR TIRE

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERALL WITH (mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
13	175/75R13	84	T	-	594	-	-	-	E	E	2
14	175/75R14	86	T	-	618	-	-	-	E	E	2
15	31x10.50R15LT	109	S	-	775	11.5	1030	350	E	C	2
	205/60R15	91	H	-	627	-	-	-	E	C	2
	205/65R15	94	H	-	647	-	-	-	E	C	2
	205/70R15	96	H	-	669	-	-	-	E	E	2
16	205/60R16	92	H	-	652	-	-	-	E	C	2
	215/65R16	98	T	221	686	9	750	300	E	E	2
	225/70R16	103	T	228	722	9	875	300	E	E	2
	245/70R16	107	T	248	750	8.8	975	300	-	-	-
	245/75R16	111	T	248	774	8.8	1090	300	E	E	2
	255/70R16	111	T	260	764	8.8	1090	300	E	C	2
	265/70R16	112	T	272	778	10	1120	300	E	E	2
	LT245/70R16	113/110	S	248	750	11	1150/1060	450	-	-	-
	LT245/75R16	120/116	S	248	774	11	1380/1260	550	-	-	-
	LT265/70R16	121/118	S	272	778	11.5	1450/1320	550	-	-	-
	LT265/75R16	123/120	Q	267	804	12.5	1550/1400	550	E	C	2
	LT285/75R16	126/123	Q	286	834	12.5	1700/1550	550	E	C	2
	LT285/75R16	126/123	R	-	-	-	-	-	E	C	2
	215/65R17	99	T	221	712	9	775	300	E	E	2
17	225/60R17	99	H	228	702	8.8	775	300	E	E	2
	265/65R17	112	T	272	776	10	1120	300	E	E	2
	265/70R17	115	S	272	804	10	1215	300	E	E	2
	265/70R17	112	T	-	-	-	-	-	E	E	2
	275/65R17	115	T	279	790	8.8	1215	300	-	-	-
	285/65R17	116	T	292	802	8.8	1250	300	-	-	-
	LT245/70R17	119/116	S	248	776	11	1360/1250	550	-	-	-
	LT245/75R17	121/118	S	248	800	11	1450/1320	550	-	-	-
	LT285/70R17	121/118	Q	-	832	12.5	1450/1320	550	E	C	2
	LT285/70R17	121/118	R	-	-	-	-	-	E	C	2
	P285/70R17	117	S	-	-	-	-	-	E	E	2
	LT295/70R17	121/118	Q	-	-	-	-	-	E	C	2
	LT295/70R17	121/118	R	-	-	-	-	-	E	C	2
	LT305/70R17	121/118	R	-	-	-	-	-	E	C	2
18	255/60R18	112	T	260	763	10	1120	340	E	E	2
	265/60R18	110	T	272	775	10	1060	300	E	E	2
	275/65R18	116	T	279	815	10	1250	300	E	E	2
	285/60R18	120	L	292	799	10	1400	340	-	-	-
	LT285/60R18	112/119	Q	-	799	12.5	1500/1360	550	E	C	2
	305/60R18	120	S	311	823	10	1400	300	E	E	2
	LT275/70R18	125/122	Q	-	843	11.5	1650/1500	550	E	C	2
	LT275/70R18	125/122	S	-	-	-	-	-	E	C	2

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERALL WITH (mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
18	285/60R18	20	S	-	799	10	400	340	E	E	2
	LT285/60R18	112/119	S	-	-	-	-	-	E	C	2
	LT285/65R18	125/122	R	292	827	11.5	1650/1500	550	E	C	2
	LT295/70R18	129/126	Q	-	-	-	-	-	E	C	2
	LT325/60R18	124/121	Q	331	847	12.5	1600/1450	450	E	C	2
	LT325/60R18	124/121	R	-	-	-	-	-	E	C	2
	LT325/65R18	127/124	Q	-	-	-	-	-	E	C	2
	LT325/65R18	127/124	R	-	879	12.5	1750/1600	450	E	C	2
20	265/50R20 XL	111	S	277	774	10	1090	340	E	E	2
	275/55R20 XL	117	S	-	810	10	1285	340	E	E	2
	285/55R20	119	S	-	822	10	1360	340	E	E	2
	285/55R20	115	S	-	-	-	-	-	E	E	2
	295/60R20	116	S	-	-	-	-	-	E	E	2
	LT295/60R20	126/123	S	-	-	-	-	-	E	C	2
	305/50R20 XL	120	S	316	814	10	1400	340	E	E	2
	LT305/55R20	121/118	S	-	-	-	-	-	E	C	2
	LT325/60R20	121/118	Q	-	-	-	-	-	E	C	2
	LT325/60R20	121/118	R	-	-	-	-	-	E	C	2
22	LT285/55R22	124/121	R	-	-	-	-	-	E	C	2
	LT325/55R22	122	R	-	-	-	-	-	E	C	2