

CARÁCTERÍSTICAS



EFICIENCIA



ADHERENCIA



SIMÉTRICA



TRACCIÓN



ON & OFF



DRENAJE

MEDIDAS	15 - 17
SERIES	70 - 85
IND. VELOCIDAD	P - Q



PASSENGER CAR TIRE

RIN	SIZE	LOAD INDEX	SPEED SYMBOL	OVERAL WITH (mm)	OVERALL DIAMETER (mm)	TREAD DEPTH (mm)	STANDAR LOAD (kg)	INFLATED PRESSURE (kPa)			
15	31X10.50R15LT	109	Q	-	775	-	-	-	-	-	-
	32X11.50R15LT	113	Q	-	-	-	-	-	-	-	-
	35X12.50R15LT	113	Q	-	887	-	-	-	-	-	-
	LT215/75R15	100/97	Q	-	-	-	-	-	-	-	-
	LT235/75R15	104/101	Q	-	733	-	-	-	-	-	-
16	LT215/85R16	115/112	Q	-	-	-	-	-	-	-	-
	LT225/75R16	115/112	N	-	-	-	-	-	-	-	-
	LT235/70R16	110/107	Q	-	736	-	-	-	-	-	-
	LT235/85R16	120/116	Q	-	806	-	-	-	-	-	-
	LT245/70R16	118/115	Q	-	750	-	-	-	-	-	-
	LT245/75R16	120/116	N	-	-	-	-	-	-	-	-
	LT265/75R16	123/120	N	-	-	-	-	-	-	-	-
	LT265/75R16	123/120	Q	-	804	-	-	-	-	-	-
	LT265/75R16	119/116	Q	-	804	-	-	-	-	-	-
	LT285/75R16	116/113	Q	-	834	-	-	-	-	-	-
	LT285/75R16	122/119	N	-	-	-	-	-	-	-	-
	LT285/75R16	126/123	Q	-	834	-	-	-	-	-	-
17	33X12.50R17LT	120	Q	-	-	-	-	-	-	-	-
	35X12.50R17LT	125	P	-	-	-	-	-	-	-	-
	35X12.50R17LT	121	Q	-	877	-	-	-	-	-	-
	LT265/70R17	121/118	Q	-	804	-	-	-	-	-	-
	LT285/70R17	121/118	Q	-	832	-	-	-	-	-	-
18	33X12.50R18LT	118	Q	-	826	-	-	-	-	-	-
	35X12.50R18LT	118	Q	-	877	-	-	-	-	-	-
	35X12.50R18LT	123	Q	-	-	-	-	-	-	-	-
20	35X12.50R20LT	121	Q	-	877	-	-	-	-	-	-
	33X12.50R20LT	114	Q	-	826	-	-	-	-	-	-